

MATERIAL SAFETY DATA SHEET

RED ADDITIVE FOR DBX2636R

Version Number 1.0
Revision Date 06/11/2002

Page 1 of 7
Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION
2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE : Product Stewardship, (314) 771-1800
Emergency telephone number : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**

Product name : RED ADDITIVE FOR DBX2636R
Product code : FO00007876
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
2-Naphthalenecarboxylic acid, 4-[(5-chloro-4-methyl-2-sulfo-phenyl)azo]-3-hydroxy-, barium salt (1:1)	7585-41-3	10 - 30
Benzoic acid, 2-[(2-hydroxy-3,6-disulfo-1-naphthalenyl)azo]-, barium salt (2:3)	15782-06-6	10 - 30

3. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Skin contact, Ingestion

Acute exposure

Inhalation : Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion : May be harmful if swallowed.
Eyes : May cause eye/skin irritation.
Skin : Experience shows no unusual dermatitis hazard from routine handling.

RED ADDITIVE FOR DBX2636R

Version Number 1.0

Page 2 of 7

Revision Date 06/11/2002

Print Date 11/4/2011

Chronic exposure : Refer to Section 11 for Toxicological Information.

Medical Conditions : None known.

Aggravated by Exposure:

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.

Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : No data available.

Flammable Limits

Upper explosion limit : No data available.

Lower explosion limit : No data available.

Autoignition temperature : Not applicable.

Suitable extinguishing media : Carbon dioxide blanket, dry powder, foam, Water spray.

Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.

Unusual Fire/Explosion Hazards : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

Environmental precautions : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

RED ADDITIVE FOR DBX2636R

Version Number 1.0

Revision Date 06/11/2002

Page 3 of 7

Print Date 11/4/2011

7. HANDLING AND STORAGE

- Handling : Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
- Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Respiratory protection : Under normal handling conditions a respirator is not required.
- Eye/Face Protection : Safety glasses with side-shields.
- Hand protection : Protective gloves.
- Skin and body protection : Long sleeved clothing.
- Additional Protective Measures : Safety shoes.
- General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
- Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

MATERIAL SAFETY DATA SHEET

RED ADDITIVE FOR DBX2636R

Version Number 1.0

Page 4 of 7

Revision Date 06/11/2002

Print Date 11/4/2011

Components	Value	Exposure time	Exposure type	List:
2-Naphthalenecarboxylic acid, 4-[(5-chloro-4-methyl-2-sulfophenyl)azo]-3-hydroxy-, barium salt (1:1)	0.5 mg/m ³	PEL:	as Ba	OSHA Z1
2-Naphthalenecarboxylic acid, 4-[(5-chloro-4-methyl-2-sulfophenyl)azo]-3-hydroxy-, barium salt (1:1)	0.5 mg/m ³	Time Weighted Average (TWA):		ACGIH
Benzoic acid, 2-[(2-hydroxy-3,6-disulfo-1-naphthalenyl)azo]-, barium salt (2:3)	0.5 mg/m ³	PEL:	as Ba	OSHA Z1
Benzoic acid, 2-[(2-hydroxy-3,6-disulfo-1-naphthalenyl)azo]-, barium salt (2:3)	0.5 mg/m ³	Time Weighted Average (TWA):		ACGIH

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: Liquid	Evaporation rate	: Not established
Appearance	: Viscous, Liquid	Specific Gravity	: Not determined
Color	: RED	Bulk density	: Not applicable.
Odor	: Very faint	Vapor pressure	: Not determined
Melting point/range	: Not applicable	Vapor density	: Not determined
Boiling Point:	: Not applicable	pH	: Not applicable.
Water solubility	: Immiscible		

10. STABILITY AND REACTIVITY

Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	: Carbon dioxide (CO ₂), carbon monoxide (CO), oxides of nitrogen (NO _x), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

MATERIAL SAFETY DATA SHEET

RED ADDITIVE FOR DBX2636R

Version Number 1.0

Page 5 of 7

Revision Date 06/11/2002

Print Date 11/4/2011

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7585-41-3	2-Naphthalenecarboxylic acid, 4-[(5-chloro-4-methyl-2-sulfophenyl)azo]-3-hydroxy-, barium salt (1:1)	Irritant	Eyes, Skin.
15782-06-6	Benzoic acid, 2-[(2-hydroxy-3,6-disulfo-1-naphthalenyl)azo]-, barium salt (2:3)	Irritant	Eyes, Skin.

12. ECOLOGICAL INFORMATION

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Environmental toxicity has not been established for this mixture as a whole.

Bioaccumulation Potential : No data available.

Additional advice : No data available.

13. DISPOSAL CONSIDERATIONS

Product : Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground) : Not regulated for transportation.

ICAO/IATA : Not regulated for transportation.

MATERIAL SAFETY DATA SHEET

RED ADDITIVE FOR DBX2636R

Version Number 1.0
Revision Date 06/11/2002

Page 6 of 7
Print Date 11/4/2011

IMO / IMDG : Not regulated for transportation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on the TSCA inventory or are exempt.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Product
2-Naphthalenecarboxylic acid, 4-[(5-chloro-4-methyl-2-sulphophenyl)azo]-3-hydroxy-, barium salt (1:1)	7585-41-3	10.90	1,000lbs	9,172 LB

California Proposition : This product does not contain a substance listed by California Prop 65.

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
BARIUM COMPOUNDS [EXCEPT BASO4]	7585-41-3	10.90
BARIUM COMPOUNDS [EXCEPT BASO4]	15782-06-6	25.51

Canadian Regulations:

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.
7585-41-3
15782-06-6

DSL : Listed.

RED ADDITIVE FOR DBX2636R

Version Number 1.0

Revision Date 06/11/2002

Page 7 of 7

Print Date 11/4/2011

National Inventories:

Australia AICS : Not determined.

China IECS : Not determined.

Europe EINECS : Listed.

Japan ENCS : Not determined.

Korea KECI : Not determined.

Philippines PICCS : Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.