

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****STAN-TONE 12VC03 YELLOW**

Version Number 1.1

Page 1 of 6

Revision Date 12/27/2012

Print Date 12/27/2012

1. PRODUCT AND COMPANY IDENTIFICATION**POLYONE CORPORATION****8155 Cobb Center Drive, Kennesaw, GA 30152**

Telephone : 1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure
number or accident).**

Product name : STAN-TONE 12VC03 YELLOW
Product code : FO20030256
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

3. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Do not use this pigment in polymers at temperatures over 200°C (392°F). Decomposition of diarylide pigments in polymers at temperatures over 200°C (392°F) may produce trace amounts of monoazo dyes, which in turn can decompose to produce aromatic amines. The amount and type of degradation products formed depend on the dwell time, formulation and processing conditions as well as temperature. As conditions become more severe, as when temperatures move into the 240-300°C (464-572°F) range, trace quantities of 3,3'-dichlorobenzidine can be generated. 3,3'-dichlorobenzidine is classified as a suspect carcinogen by NTP and IARC, is classified as Acute Toxicity category 4 and Carcinogen Category 1B according to 1272/2008EC (CLP), and is regulated by OSHA as a suspect carcinogen. In order to avoid the generation of and exposure to 3,3'-dichlorobenzidine, do not use diarylide pigments in polymers when temperatures exceed 200°C (392°F). Handle with care. Organic dusts have the potential to be explosive with static spark or flame initiation.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Skin contact, Ingestion

Acute exposure

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

STAN-TONE 12VC03 YELLOW

Version Number 1.1

Revision Date 12/27/2012

Page 2 of 6

Print Date 12/27/2012

- Inhalation : Resin particles, like other inert materials, can be mechanically irritating.
- Ingestion : May be harmful if swallowed.
- Eyes : Particulates, like other inert materials can be mechanically irritating.
- Skin : Experience shows no unusual dermatitis hazard from routine handling.

Chronic exposure : Refer to Section 11 for Toxicological Information.

Medical Conditions Aggravated by Exposure: : None known.

4. FIRST AID MEASURES

- Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
- Ingestion : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
- Eyes : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
- Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIREFIGHTING MEASURES

- Flash point : not applicable
- Flammable Limits
 - Upper explosion limit : not applicable
 - Lower explosion limit : not applicable
- Auto-ignition temperature : Not relevant
- Suitable extinguishing media : Carbon dioxide blanket, Water spray, Dry powder, Foam.
- Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
- Unusual Fire/Explosion Hazards : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

STAN-TONE 12VC03 YELLOW

Version Number 1.1

Page 3 of 6

Revision Date 12/27/2012

Print Date 12/27/2012

- Environmental precautions : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
- Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.

7. HANDLING AND STORAGE

- Handling : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
- Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Respiratory protection : No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.
- Eye/Face Protection : Safety glasses with side-shields
- Hand protection : Protective gloves
- Skin and body protection : Long sleeved clothing
- Additional Protective Measures : Safety shoes
- General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
- Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

There are no known hazardous components above regulatory thresholds in this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

- | | | | |
|---------------------|--------------------|------------------|------------------|
| Form | : solid | Evaporation rate | : Not applicable |
| Appearance | : powder, granular | Specific Gravity | : Not determined |
| Colour | : YELLOW | Bulk density | : Not determined |
| Odour | : very faint | Vapour pressure | : not applicable |
| Melting point/range | : Not determined | Vapour density | : not applicable |
| Boiling Point: | : not applicable | pH | : not applicable |
| Water solubility | : insoluble | | |

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

STAN-TONE 12VC03 YELLOW

Version Number 1.1
Revision Date 12/27/2012

Page 4 of 6
Print Date 12/27/2012

10. STABILITY AND REACTIVITY

- Stability : The product is stable if stored and handled as prescribed.
- Hazardous Polymerization : Will not occur.
- Conditions to avoid : To avoid thermal decomposition, do not overheat. Keep away from oxidizing agents and open flame.
- Incompatible Materials : Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
- Hazardous decomposition products : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride. Do not use this pigment in polymers at temperatures over 200°C (392°F). Decomposition of diarylide pigments in polymers at temperatures over 200°C (392°F) may produce trace amounts of monoazo dyes, which in turn can decompose to produce aromatic amines. The amount and type of degradation products formed depend on the dwell time, formulation and processing conditions as well as temperature. As conditions become more severe, as when temperatures move into the 240-300°C (464-572°F) range, trace quantities of 3,3'-dichlorobenzidine can be generated. 3,3'-dichlorobenzidine is classified as a suspect carcinogen by NTP and IARC, is classified as Acute Toxicity category 4 and Carcinogen Category 1B according to 1272/2008EC (CLP), and is regulated by OSHA as a suspect carcinogen. In order to avoid the generation of and exposure to 3,3'-dichlorobenzidine, do not use diarylide pigments in polymers when temperatures exceed 200°C (392°F). Handle with care. Organic dusts have the potential to be explosive with static spark or flame initiation.

11. TOXICOLOGICAL INFORMATION

There are no known hazardous components above regulatory thresholds in this product.

12. ECOLOGICAL INFORMATION

- Persistence and degradability : Not readily biodegradable.
- Environmental Toxicity : Adverse ecological impact is not known or expected under normal use.
- Bioaccumulation Potential : no data available
- Additional advice : no data available

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

STAN-TONE 12VC03 YELLOW

Version Number 1.1
Revision Date 12/27/2012

Page 5 of 6
Print Date 12/27/2012

13. DISPOSAL CONSIDERATIONS

- Product : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
- Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

- U.S. DOT Classification : Not regulated for transportation.
- ICAO/IATA : Not regulated for transportation.
- IMO/IMDG (maritime) : Not regulated for transportation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : There are no known hazardous components above regulatory thresholds in this product.

TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)
not applicable

California Proposition 65 : WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

STAN-TONE 12VC03 YELLOW

Version Number 1.1
Revision Date 12/27/2012

Page 6 of 6
Print Date 12/27/2012

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

not applicable

WHMIS Classification : Not controlled.

DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Not determined

China IECS : Not determined

Europe EINECS : Listed

Japan ENCS : Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.